

NORTHERN ENERGY BATTERIES®

BCI	Part Number	Performance Data				Dimensions						Warranty Service
		@ 0.F	@ 32.F	R/C	Volts	L	W	H	L	W	H	Free / Prorate
		@ -18.C	@ 0.C	@ 25 A		IN	IN	IN	MM	MM	MM	
Deep Cycle												
24DC	24DC	N/A	N/A	130	12V	11.2	6.7	9.7	286	171	248	12/24
24HDC	24HDC	N/A	N/A	150	12V	11.2	6.7	9.7	284	171	246	12/36
27DC	27DC	N/A	N/A	150	12V	12.8	6.7	9.8	324	171	248	12/24
27HDC	27HDC	N/A	N/A	180	12V	12.8	6.7	9.8	324	171	248	12/36
31DC	31DC	650	800	210	12V	13.0	6.8	9.4	330	171	248	12/36
8DDC	8DDC	N/A	N/A	450	12V	20.6	11.2	9.5	523	284	241	12/36
GC2-6V	GC232	232 amp hr.		470	6V	10.4	7.1	10.9	264	181	276	24/40
Marine Starting												
24MS	24MS600	480	600	70	12V	11.2	6.7	9.7	284	171	246	12/24
24MS	24MS800	700	875	120	12V	11.2	6.7	9.7	284	171	246	12/24
24MS	24MS1000	800	1000	145	12V	11.2	6.7	9.7	284	171	246	12/24
27MS	27MS1000	800	1000	145	12V	12.8	6.7	9.8	324	171	248	12/24
Commercial												
1	G1	625	780	150	6V	8.9	6.7	8.7	226	170	221	12/36
2	G2	625	780	150	6V	10.2	6.7	8.7	259	170	221	12/36
31S	31S-1000	750	950	170	12V	13.0	6.8	9.4	330	173	240	12
31S	31S-1200	950	1150	190	12V	13.0	6.8	9.4	330	173	240	24/24
31A	31P-1200	950	1150	190	12V	13.0	6.8	9.4	330	173	240	24/24
31A	31P-1300	1000	1250	200	12V	13.0	6.8	9.4	330	173	240	36/36
31S	31S-1300	1000	1250	200	12V	13.0	6.8	9.4	330	173	240	36/36
4D	4D-1250	1000	1250	300	12V	20.5	8.6	9.5	521	218	241	12/36
4DLT	4DLT	900	1200	260	12V	19.9	8.2	7.9	505	208	201	12/30
8D	8D-1375	1100	1375	310	12V	20.6	11.2	9.5	523	284	241	12/36
8D	8D-1625	1300	1625	390	12V	20.6	11.2	9.5	523	284	241	12/36
8D	8D-MF	1300	1600	380	12V	20.6	11.2	9.5	523	284	241	18/36

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

WANNA "START" SOMETHING
Ph: 604-588-7445 or Fax: 604-588-7405